

JPL D-94634

ECOsysteM Spaceborne Thermal Radiometer Experiment on Space Station (ECOSTRESS) Mission

Level 1 Product Specification Document

June 13, 2019

Thomas Logan, Michael Smyth, Eugene Chu
ECOSTRESS Algorithm Development Team

National Aeronautics and
Space Administration



Jet Propulsion Laboratory
4800 Oak Grove Drive
Pasadena, California 91109-8099
California Institute of Technology

© 2018 California Institute of Technology. Government sponsorship acknowledged

ECOSTRESS Level 1 Product Specification Document

Prepared by:

Thomas L. Logan
ECOSTRESS Algorithm Development Team

Date

Mike M. Smyth
ECOSTRESS Algorithm Development Team

Date

Eugene Chu
ECOSTRESS SDS System Engineer

Date

Approved by:

Dana Freeborn
ECOSTRESS Mission System Manager

Date

Concurred by:

Simon Hook
ECOSTRESS Principal Investigator

Date

National Aeronautics and
Space Administration



Jet Propulsion Laboratory
4800 Oak Grove Drive
Pasadena, California 91109-8099
California Institute of Technology

*** Original signature page on file in project physical repository ***

Document Change Log

Revision	Date	Sections Changed	Author
Preliminary	02/23/2016	All	Tom Logan Mike Smyth
	06/06/2016	T2-1, T2-2, T3-1	Eugene Chu
	07/26/2016	3.0, 3.1	Eugene Chu
	7/27/2016	T3-8, T3-9	Mike Smyth
	08/02/2016	3.0, 3.1	Eugene Chu
	12/16/2016	3.1, 3.3	Mike Smyth
	02/10/2017	3.3, 4.1, Appendix A	Eugene Chu Tom Logan
	12/05/2017	3.0, 3.3, 4.1	Eugene Chu Tom Logan Mike Smyth
	4/11/2018	3.3	Mike Smyth
	6/28/2018	3.3 Added FPIE encoder values	Mike Smyth
	8/13/2018	4.1.1 Added L1A_RAW_PIX metadata	Eugene Chu
	10/2/2018	3.3 Add L1B_MAP_RAD table	Mike Smyth
	2019-02-28	Added valid min/max/fill to product tables.	Eugene Chu
	2019-05-15	Updates for new acquisition mode with 3 band data	Eugene Chu Tom Logan
	2019-0613	Minor change to overview	Eugene Chu

Section/Page	Description	Date

Contacts

Readers seeking additional information about this document may contact the following ECOSTRESS Algorithm Development team members:

Eugene Y. Chu

MS 168-414

Jet Propulsion Laboratory

4800 Oak Grove Drive

Pasadena CA 91109

Email: Eugene.Y.Chu@jpl.nasa.gov

Office: (818) 354-6496

Thomas L. Logan

MS 169-414

Jet Propulsion Laboratory

4800 Oak Grove Drive

Pasadena CA 91109

Email: Thomas.L.Logan@jpl.nasa.gov

Office: (818) 354-4032

Michael M. Smyth

MS 169-315

Jet Propulsion Laboratory

4800 Oak Grove Drive

Pasadena CA 91109

Email: Michael.M.Smyth@jpl.nasa.gov

Office: (818) 354-9812

TABLE OF CONTENTS

Table of Contents	6
1.0 Introduction	7
1.1 Identification	7
1.2 Purpose and Scope	7
1.3 Mission Overview	7
1.4 Applicable and Reference Documents	8
1.4.1 Applicable Documents.....	8
1.4.2 Reference Documents	8
1.5 ECOSTRESS Data Products	8
2.0 Data Product Organization	10
2.1 Product File Format	10
2.2 HDF5 Notation	10
2.2.1 HDF5 File.....	10
2.2.2 HDF5 Group	10
2.2.3 HDF5 Dataset.....	10
2.2.4 HDF5 Datatype.....	10
2.2.5 HDF5 Dataspace	11
2.2.6 HDF5 Attribute	11
2.3 ECOSTRESS File Organization	12
2.3.1 Structure.....	12
2.3.2 Data.....	12
2.3.3 Element Types.....	12
2.3.4 File Level Metadata	12
2.3.5 Local Metadata.....	13
2.4 Data Definition Standards	13
2.4.1 Double Precision Time Variables	14
2.4.2 Array Representation.....	14
3.0 ECOSTRESS Product Files	15
3.1 Standard Metadata	16
3.2 Product-Specific Metadata	17
3.3 Product Data	17
3.3.1 L1A_ENG - Spacecraft and Engineering Data.....	17
3.3.2 L1A_BB - FPA Blackbody Calibration DN	17
L1A_PIX - Raw Pixel Data with FPA Blackbody Temperature and Processed FPA BlackBody Band DNs	19
3.3.3 L1B_RAD - Radiometrically Corrected and Resampled At-Sensor Radiances	20
3.3.4 L1B_GEO - Latitude and Longitude Geolocations, solar and view angles.....	21
3.3.5 L1B_ATT - Corrected spacecraft ephemeris and attitude data.....	22
3.3.6 L1B_MAP_RAD - Map projected radiance	23
3.4 Product Metadata File	24
4.0 APPENDIX A: intermediate and Non-delivered products	25
4.1 Intermediate, Temporary, and other non-delivered products	25
4.1.1 L1A_RAW_PIX - Raw Scene Pixel Data	25
4.1.2 L1A_RAW_ATT - Uncorrected Spacecraft Ephemeris and Attitude Data.....	26
4.1.3 L1A_RAD_GAIN - Gain and offset coefficients and optional radiance and temperature Images	26
4.1.4 L1B_GEO_QA - QA data for L1B_GEO PGE.....	27

1.0 INTRODUCTION

1.1 Identification

This is the Product Specification Document (PSD) for Level 1 (L1) data products of the ECOSystem Spaceborne Thermal Radiometer Experiment on Space Station (ECOSTRESS) project. The ECOSTRESS L1 products provide corrected spacecraft attitude, calibrated at-sensor radiances and geolocation tags of each pixel data acquired by the ECOSTRESS radiometer instrument according to the algorithm described in the ECOSTRESS L1 Geolocation Algorithm Theoretical Basis Document (ATBD) (JPL D-94641) and ECOSTRESS L1 Calibration ATBD.

1.2 Purpose and Scope

This Product Specification Document (PSD) describes the standard Level 1 radiance, geolocation, and attitude products generated in the ECOSTRESS SDS at JPL. These include the detailed descriptions of the format and contents of the product and ancillary files that will be delivered to the Land Process Distributed Active Archive Center (LP-DAAC).

1.3 Mission Overview

The ECOSTRESS instrument measures the temperature of plants and uses that information to better understand how much water plants need and how they respond to stress.

ECOSTRESS addresses three overarching science questions:

- How is the terrestrial biosphere responding to changes in water availability?
- How do changes in diurnal vegetation water stress impact the global carbon cycle?
- Can agricultural vulnerability be reduced through advanced monitoring of agricultural water consumptive use and improved drought estimation?

The ECOSTRESS mission answers these questions by accurately measuring the temperature of plants. Plants regulate their temperature by releasing water through tiny pores on their leaves called stomata. If they have sufficient water, they can maintain their temperature. However, if there is insufficient water, their temperatures rise. This temperature rise can be measured with a sensor in space. ECOSTRESS uses a multispectral thermal infrared (TIR) radiometer to measure the surface temperature, deployed on the International Space Station. The instrument will measure radiances at 5 spectral bands in the 8-12.5 μm range with approximately 38 meter by 57 meter of spatial resolution on the ground.

On September 29th 2018, ECOSTRESS experienced an anomaly with its primary mass storage unit (MSU). ECOSTRESS has a primary and secondary MSU (A and B). On December 5th, the instrument was switched to the secondary MSU and operations resumed with initial acquisitions over Australia and wider coverage resumed on January 9th 2019. The initial anomaly was attributed to exposure to high radiation regions, primarily over the Southern Atlantic Anomaly, and the acquisition strategy was revised to exclude these regions from future acquisitions. On March 14th 2019, the secondary MSU experienced an anomaly, and acquisitions are temporarily on hold. Work is underway to implement a direct streaming option, which will bypass the need for mass storage units. The streaming acquisition mode will change the format of the data being

collected. Specifically, the new collection mode will eliminate the 1.6 μm (SWIR), 8.2 μm (TIR), and 9.0 μm (TIR) bands. To simplify product formats, the L1 and L2 products will continue to contain the datasets for these bands, but the datasets will contain fill values. This will be seen in products generated after May 15th 2019, when the instrument resumes operations. These changes will be described in the detailed product specifications.

1.4 Applicable and Reference Documents

“Applicable” documents levy requirements on the areas addressed in this document. “Reference” documents are identified in the text of this document only to provide additional information to readers. Unless stated otherwise, the document revision level is Initial Release. Document dates are not listed, as they are redundant with the revision level.

1.4.1 Applicable Documents

1. ECOSTRESS Project Level 3 Science Data System Requirements (JPL D-94088).
2. ECOSTRESS Science Data Management Plan (JPL D-94607)
3. 423-ICD-005 ICD Between ECOSTRESS SDS and LPDAAC
4. ECOSTRESS Level 1 Geolocation Algorithm Theoretical Basis Document (JPL D-94641)
5. ECOSTRESS Level 1 Calibration Algorithm Theoretical Basis Document (JPL D-94642)
6. ECOSTRESS Level 1 Algorithm Specification Document
7. TBA

1.4.2 Reference Documents

1.5 ECOSTRESS Data Products

The ECOSTRESS mission will generate 13 different distributable data products. The products represent four levels of data processing, with data granules defined as an image scene. Each image scene consists of 44 scans of the instrument mirror, each scan taking approximately 1.181 seconds, and each image scene taking approximately 52 seconds. Each image scene starts at the beginning of the first target area encountered during each orbit. Each orbit is defined as the equatorial crossing of an ascending International Space Stations (ISS) orbit.

ECOSTRESS Level 0 data include spacecraft packets that have been pre-processed by the Ground Data System (GDS). Level 1 products include spacecraft engineering data, the time-tagged raw sensor pixels appended with their radiometric calibration coefficients, the black body pixels used to generate the calibration coefficients, geolocated and radiometrically calibrated at-sensor radiances of each image pixel, the geolocation tags of each pixel, and the corrected spacecraft attitude data. Level 2 products include the land surface temperature and emissivities of each spectral band retrieved from the at-sensor radiance data, and a cloud mask. Level 2 products also appear in image scene granules. Level 3 products contain evapotranspiration data derived from Level 2 data. Level 4 products contain evaporative stress index and water use efficiency derived from Level 3 data.

The ECOSTRESS products are listed in Table 1-1. This document will discuss the Level 0 (not-delivered) and Level 1 products.

Table 1-1: ECOSTRESS Distributable Standard Products

Product type	Description
L0A_FLEX	Level 0 “raw” spacecraft packets
L0A_HK	Level 0 housekeeping packets
L1A_ENG	Spacecraft and instrument engineering data, including blackbody gradient coefficients
L1A_BB	Instrument Black Body calibration pixels
L1A_PIX	Raw pixel data with appended calibration coefficients
L1B_GEO	Geolocation tags, sun angles, and look angles, and calibrated, resampled at-sensor radiances
L1B_RAD	Radiometrically corrected, band-aligned, squared at-sensor radiance pixels
L1B_MAP_RAD	L1B_RAD data map projected to fixed 70 meter pixels
L1B_ATT	Corrected spacecraft ephemeris and attitude data
L2_LSTE	Land Surface temperature and emissivity
L2_CLOUD	Cloud mask
L3_ET_PT-JPL	Evapotranspiration retrieved from L2_LSTE using the PT-JPL Algorithm
L3_ET_ALEXI-USDA	Evapotranspiration generated at USDA with the ALEXI/DisALEXI Algorithm over specific calibration sites
L4_ESI_PT-JPL	Evaporative Stress Index generated with PT-JPL
L4_ESI_ALEXI-USDA	Evaporative Stress Index generated at USDA with the ALEXI/DisALEXI over specific calibration sites
L4_WUE	Water Use efficiency
L3_L4_QA	Quality Assessment fields for all ancillary data used in L3 and L4 products

2.0 DATA PRODUCT ORGANIZATION

2.1 Product File Format

All ECOSTRESS standard products are in the Hierarchical Data Format version 5 (HDF5). HDF5 is a general purpose file format and programming library for storing scientific data. The National Center for Supercomputing Applications (NCSA) at the University of Illinois developed HDF to help scientists share data regardless of the source. The following sections provide some key elements of HDF5 that will be employed in ECOSTRESS data products. Complete documentation of the HDF5 structure and application software can be found at <http://www.hdfgroup.org/HDF5>

2.2 HDF5 Notation

The key concepts of the HDF5 Abstract Data Model are Files, Groups, Datasets, Datatypes, Attributes and Property Lists. The following sections provide a brief description of each of these key HDF5 concepts.

2.2.1 HDF5 File

A File is the abstract representation of a physical data file. Files are containers for HDF5 Objects. These Objects include Groups, Datasets, and Datatypes.

2.2.2 HDF5 Group

Groups are containers for other Objects, including Datasets, named Datatypes and other Groups. In that sense, groups are analogous to directories that are used to categorize and classify files in standard operating systems.

The notation for files is identical to the notation used for Unix directories. The root Group is “/”. Like Unix directories, Objects appear in Groups through “links”. Thus, the same Object can simultaneously be in multiple Groups.

2.2.3 HDF5 Dataset

The Dataset is the HDF5 component that stores user data. Each Dataset associates with a Dataspace that describes the data dimensions, as well as a Datatype that describes the basic unit of storage element. A Dataset can also have Attributes.

2.2.4 HDF5 Datatype

A Datatype describes a unit of data storage for Datasets and Attributes. Datatypes are subdivided into Atomic and Composite Types.

Atomic Datatypes are analogous to simple basic types in most programming languages. HDF5 Atomic Datatypes include Time, Bitfield, String, Reference, Opaque, Integer, and Float. Each atomic type has a specific set of properties. Examples of the properties associated with Atomic Datatypes are:

- Integers are assigned size, precision, offset, pad byte order, and are designated as signed or unsigned.
- Strings can be fixed or variable length, and may or may not be null-terminated.
- References are constructs within HDF5 Files that point to other HDF5 Objects in the same file.

HDF5 provides a large set of predefined Atomic Datatypes. Table 2-1 lists the Atomic Datatypes that are used in ECOSTRESS data products.

Table 2-1: HDF5 Atomic Datatypes

HDF5 Atomic Datatypes	Description
H5T_STD_U8LE	unsigned, 8-bit, little-endian integer
H5T_STD_U16LE	unsigned, 16-bit, little-endian integer
H5T_STD_U32LE	unsigned, 32-bit, little-endian integer
H5T_STD_U64LE	unsigned, 64-bit, little-endian integer
H5T_STD_I8LE	signed, 8-bit, little-endian integer
H5T_STD_I16LE	signed, 16-bit, little-endian integer
H5T_STD_I32LE	signed, 32-bit, little-endian integer
H5T_STD_I64LE	Signed, 64-bit, little-endian integer
H5T_IEEE_F32LE	32-bit, little-endian, IEEE floating point
H5T_IEEE_F64LE	64-bit, little-endian, IEEE floating point
H5T_STRING	character string made up of one or more bytes

Composite Datatypes incorporate sets of Atomic datatypes. Composite Datatypes include Array, Enumeration, Variable Length and Compound.

- The Array Datatype defines a multi-dimensional array that can be accessed atomically.
- Variable Length presents a 1-D array element of variable length. Variable Length Datatypes are useful as building blocks of ragged arrays.

Named Datatypes are explicitly stored as Objects within an HDF5 File. Named Datatypes provide a means to share Datatypes among Objects. Datatypes that are not explicitly stored as Named Datatypes are stored implicitly. They are stored separately for each Dataset or Attribute they describe.

None of the ECOSTRESS data products employ Enumeration or Compound data types.

2.2.5 HDF5 Dataspace

A Dataspace describes the rank and dimension of a Dataset or Attribute. For example, a “Scalar” Dataspace has a rank of 1 and a dimension of 1. Thus, all subsequent references to “Scalar” Dataspace in this document imply a single dimensional array with a single element.

Dataspaces provide considerable flexibility to HDF5 products. They incorporate the means to subset associated Datasets along any or all of their dimensions. When associated with specific properties, Dataspaces also provide the means for Datasets to expand as the application requires.

2.2.6 HDF5 Attribute

An Attribute is a small aggregate of data that describes Groups or Datasets. Like Datasets, Attributes are also associated with a particular Dataspace and Datatype. Attributes cannot be subsetting or extended. Attributes themselves cannot have Attributes.

2.3 ECOSTRESS File Organization

2.3.1 Structure

ECOSTRESS data products follow a common convention for all HDF5 Files. Use of this convention provides uniformity of data access and interpretation.

The ECOSTRESS Project uses HDF5 Groups to provide an additional level of data organization. All metadata that pertain to the complete data granule are members of the “/Metadata” Group. All other data are organized within Groups that are designed specifically to handle the structure and content of each particular data product.

2.3.2 Data

All data in HDF5 files are stored in individual Datasets. All related Datasets in an ECOSTRESS product are assigned to an HDF5 Group. A standard field name is associated with each Dataset. The field name is a unique string identifier. The field name corresponds to the name of the data element the Dataset stores. This document lists these names with the description of each data element that they identify.

Each Dataset is associated with an HDF5 Dataspace and an HDF5 Datatype. They provide a minimally sufficient set of parameters for reading the data using standard HDF5 tools.

2.3.3 Element Types

ECOSTRESS HDF5 employs the Data Attribute “Type” to classify every data field as a specific data type. The “Type” is an embellishment upon the standard HDF5 Datatypes that is designed specifically to configure ECOSTRESS data products.

Table 2-2 lists all of the “Type” strings that appear in the ECOSTRESS data products. The table maps each ECOSTRESS “Type” to a specific HDF5 Datatype in both the HDF5 file and in the data buffer. The table also specifies the common conceptual data type that corresponds to the “Type” in ECOSTRESS executable code.

Table 2-2: Element Type Definitions

Type	HDF5 Datatype (File)	HDF5 Datatype (Buffer)	Conceptual Type
Unsigned8	H5T_STD_U8LE	H5T_NATIVE_UCHAR	unsigned integer
Unsigned16	H5T_STD_U16LE	H5T_NATIVE_USHORT	unsigned integer
Unsigned32	H5T_STD_U32LE	H5T_NATIVE_UINT	unsigned integer
Unsigned64	H5T_STD_U64LE	H5T_NATIVE_ULLONG	unsigned integer
Signed8	H5T_STD_I8LE	H5T_NATIVE_SCHAR	signed integer
Signed16	H5T_STD_I16LE	H5T_NATIVE_SHORT	signed integer
Signed32	H5T_STD_I32LE	H5T_NATIVE_INT	signed integer
Signed64	H5T_STD_I64LE	H5T_NATIVE_LLONG	signed integer
Float32	H5T_IEEE_F32LE	H5T_NATIVE_FLOAT	floating point
Float64	H5T_IEEE_F64LE	H5T_NATIVE_DOUBLE	floating point
VarLenStr	H5T_STRING	H5T_NATIVE_CHAR	character string

2.3.4 File Level Metadata

All metadata that describe the full content of each granule of the ECOSTRESS data product are stored within the explicitly named “/Metadata” Group. Metadata are handled using exactly the same procedures as those that are used to handle data. The contents of each Attribute that stores

metadata conform to one of the ECOSTRESS Types. Most metadata elements are stored as scalars. A few metadata elements are stored as arrays. The metadata appear in a set of HDF5 Groups under the “/Metadata” Group. These HDF5 Groups contain a set of HDF5 Attributes.

2.3.5 Local Metadata

ECOSTRESS standards incorporate additional metadata that describe each HDF5 Dataset within the HDF5 file. Each of these metadata elements appear in an HDF5 Attribute that is directly associated with the HDF5 Dataset. Wherever possible, these HDF5 Attributes employ names that conform to the Climate and Forecast (CF) conventions. Table 2-3 lists the CF names for the HDF5 Attributes that ECOSTRESS products typically employ.

Table 2-3: ECOSTRESS Specific Local Attributes

CF Compliant Attribute Name	Description	Required?
units	Units of measure. Appendix A lists applicable units for various data elements in this product.	Yes
valid_max	The largest valid value for any element in the Dataset. The data type in valid_max matches the type of the associated Dataset. Thus, if the associated Dataset stores float32 values, the corresponding valid_max will also be float32.	No
valid_min	The smallest valid value for any element in the Dataset. The data type in valid_min matches the type of the associated Dataset. Thus, if the associated Dataset stores float32 values, the corresponding valid_min will also be float32.	No
_FillValue	Specification of the value that will appear in the Dataset when an element is missing or undefined. The data type of _FillValue matches the type of the associated Dataset. Thus, if the associated Dataset stores float32 values, the corresponding _FillValue will also be float32.	Yes for all numeric data types
long_name	A descriptive name that clearly describes the content of the associated Dataset.	Yes

2.4 Data Definition Standards

The following sections of this document specify the characteristics and definitions of every data element stored in the ECOSTRESS data products. Table 2-4 defines each of the specific characteristics that are listed in those sections. Some of these characteristics correspond with the ECOSTRESS HDF5 Attributes that are associated with each Dataset. Data element characteristics that correspond to ECOSTRESS HDF5 Attributes bear the same name. The remaining characteristics are descriptive data that help users better understand the data product content.

In some situations, a standard characteristic may not apply to a data element. In those cases, the field contains the character string 'n/a'. Hexadecimal representation sometimes indicates data content more clearly. Numbers represented in hexadecimal begin with the character string '0x'.

Table 2-4: Data Element Characteristic Definitions

Characteristic	Definition
Type	The data representation of the element within the storage medium. The storage class specification must conform to a valid ECOSTRESS type.
Units	Units of measure. Typical values include “deg”, “degC”, “Kelvin”, “meters/second”, “meters”, “m**2”, “seconds” and “counts”. Appendix A includes references to important data measurement unit symbols.

2.4.1 Double Precision Time Variables

ECOSTRESS double precision time variables contain measurements relative to the J2000 epoch. Thus, these variables represent a real number of Standard International (SI) compatible seconds since 11:58:55.816 on January 1, 2000 UTC.

2.4.2 Array Representation

This document employs array notation to demonstrate and clarify the correspondence among data elements in different product data elements. The array notation adopted in this document is similar to the standards of the Fortran programming language. Indices are one based. Thus, the first index in each dimension is one. This convention is unlike C or C++, where the initial index in each dimension is zero. In multidimensional arrays, the leftmost subscript index changes most rapidly. Thus, in this document, array elements ARRAY(15,1,5) and ARRAY(16,1,5) are stored contiguously.

HDF5 is designed to read data seamlessly regardless of the computer language used to write an application. Thus, elements that are contiguous using the dimension notation in this document will appear in contiguous locations in arrays for reading applications in any language with an HDF5 interface.

This document differentiates among array indices based on relative contiguity of storage of elements referenced with consecutive numbers in that index position. A faster or fastest moving index implies that the elements with consecutive numbers in that index position are stored in relative proximity in memory. A slower or slowest moving index implies that the elements referenced with consecutive indices are stored more remotely in memory. For instance, given array element ARRAY(15,1,5) in Fortran, the first index is the fastest moving index and the third index is the slowest moving index. On the other hand, given array element array[4][0][14] in C, the first index is the slowest moving index and the third index is the fastest moving index.

3.0 ECOSTRESS PRODUCT FILES

Each ECOSTRESS product file will contain at least 3 groups of data: A standard metadata group that specifies the same type of contents for all products, a product specific metadata group that specifies those metadata elements that are useful for defining attributes of the product data, and the group(s) containing the product data. (Note: A product metadata is not to be confused with a HDF5 object metadata.)

All product file names will have the form:

```
ECOSTRESS_<PROD_TYPE>_<OOOOO>_<SSS>_<YYYYMMDD>T<hhmmss>_<BBbb>_<VV>.<TYPE>
```

Where:

PROD_TYPE: Product type =

- L0A_FLEX, Raw instrument data packets (non-distributed)
- L0A_HK, Raw instrument engineering and housekeeping packets (non-distributed)
- L1A_PIX, Time-tagged, image frames formed from L0A_FLEX packets
- L1A_BB, Calibration black body pixels recorded from instrument with each image frame
- L1A_ENG, Orbital engineering data
- L1B_RAD, Calibrated at-sensor radiance image frames
- L1B_MAP_RAD, L1B_RAD product mapped projected to fixed 70 meter pixels
- L1B_GEO, Geolocation parameters of image frames
- L1B_ATT, Refined spacecraft orbital attitude and ephemeris parameters
- L2_LSTE, Land surface Temperature and Emissivity data
- L2_CLOUD, Level 2 Cloud mask data
- L3_ET_PT-JPL, Evapotranspiration generated by JPL with PT-JPL
- L3_ET_ALEXI, Evapotranspiration generated by JPL with ALEXI/DisALEXI
- L3_ET_ALEXI-USDA, Evapotranspiration generated by USDA with ALEXI/DisALEXI
- L4_ESI_PT-JPL, Evaporative Stress Index generated by JPL with PT-JPL
- L4_ESI_ALEXI, Evaporative Stress Index generated by JPL with ALEXI/DisALEXI
- L4_ESI_ALEXI-USDA, Evaporative Stress Index generated by USDA with ALEXI/DisALEXI
- L4_WUE, Water Use Efficiency generated by JPL
- L3_L4_QA, Quality Assessment fields for all ancillary data used in L3 and L4 products generated by JPL

OOOOO: Orbit number; starting at start of mission, ascending equatorial crossing

SSS: Scene ID; starting at first scene of each orbit

YYYYMMDD: Year, month, day of scene start time

hhmmss: Hour, minute, second of scene start time

BBbb: Build ID of software that generated product, Major+Minor (2+2 digits)

VV: Product version number (2 digits)

TYPE: File type extension=

h5 for the data file

h5.met for the metadata file.

A SITE name is added to the ALEXI-USDA file name:

```
ECOSTRESS_<PROD_TYPE>_<OOOOO>_<SSS>_<YYYYMMDD>T<hhmmss>_<BBbb>_<VV>_<SITE>.<TYPE>
```

Band Ordering of L1A_PIX, L1A_BB, L1B_RAD data:

- B1 SWIR 1.66 microns
- B2 TIR 8.285 microns
- B3 TIR 8.785 microns
- B4 TIR 9.060 microns
- B5 TIR 10.522 microns
- B6 TIR 12.001 microns

3.1 Standard Metadata

This is the minimal set of metadata that must be included with each product file. The standard metadata consists of the following:

Table 3-1: Standard Product Metadata

Name	Type	Size	Example
Group	StandardMetadata		
AncillaryInputPointer	String	variable	Group name of ancillary file list
AutomaticQualityFlag	String	variable	PASS/FAIL (of product data)
BuildID	String	variable	
CampaignShortName	String	variable	Primary
CollectionLabel	String	variable	
DataFormatType	String	variable	NCSAHDF5
DayNightFlag	String	variable	
EastBoundingCoordinate	LongFloat	8	
HDFVersionID	String	variable	1.8.16
ImageLines	Int32	4	11264 (5632, 5400)
ImageLineSpacing	Float32	4	68.754
ImagePixels	Int32	4	5400 (128 for BB)
ImagePixelSpacing	Float32	4	65.536
InputPointer	String	variable	
InstrumentShortName	String	variable	ECOSTRESS
LocalGranuleID	String	variable	
LongName	String	variable	ECOSTRESS
NorthBoundingCoordinate	LongFloat	8	
PGENAME	String	variable	L1B_GEO, (L1A_RAW, L1A_CAL, L1B_Resample)
PGEVersion	String	variable	
PlatformLongName	String	variable	ISS
PlatformShortName	String	variable	ISS
PlatformType	String	variable	Spacecraft
ProcessingLevelID	String	variable	1
ProcessingLevelDescription	String	variable	Level 1 Geolocation Parameters
ProducerAgency	String	variable	JPL
ProducerInstitution	String	variable	Caltech
ProductionDateTime	String	variable	
ProductionLocation	String	variable	
RangeBeginningDate	String	variable	
RangeBeginningTime	String	variable	
RangeEndingDate	String	variable	
RangeEndingTime	String	variable	
RegionID	String	variable	
SceneID	String	variable	
ShortName	String	variable	L1B_GEO, (L1A_RAW, L1A_CAL, L1B_RAD)
SISName	String	variable	
SISVersion	String	variable	
SouthBoundingCoordinate	LongFloat	8	
StartOrbitNumber	String	variable	
StopOrbitNumber	String	variable	
WestBoundingCoordinate	LongFloat	8	

3.2 Product-Specific Metadata

Any additional metadata necessary for describing the product will be recorded in this group.

Table 3-2: Product Specific Metadata

Name	Type	Size	Example
Group	L1GEOMetadata (L1AUNCALMetadata, L1AENG...)		
AncillaryFiles	Int	4	100
AncillaryFile1	String	variable	MOD10A1.A2012129.h01v08.005.2012131060718.hdf
...			

3.3 Product Data

The product data will be stored in the following groups.

3.3.1 L1A_ENG – Spacecraft and Engineering Data

Table 3-3: Product Data Definitions

Field Name	Type	Units	Field Data	valid min	valid max	fill
Group	rtdBlackbodyGradients (Size Unlimited, 1 set per second, through entire orbit)					
RTD_325K	Float32	Kelvin	5 temperature measurements from back of Hot Black Body (HBB)	310	330	N/A
RTD_295K	Float32	Kelvin	5 temperature measurements from back of Cold Black Body (CBB)	275	305	N/A
Time_j2000	Float64	Seconds	J2000 times of temperature reading and HK packet	N/A	N/A	N/A

3.3.2 L1A_BB - FPA Blackbody Calibration DN

Table 3-4: Product Data Definitions

Field Name	Type	Units	Field Data	valid min	valid max	fill
Group	L1A_BBMetadata					
QAPercentMissing Data	Float32	%	Percentage of data missing from L0B	0	100	N/A
BandSpecification	Float32	μm	Wavelength of BB pixel data in corresponding datasets for bands 1 through 6: 1.6, 8.2, 8.7,9.0, 10.5, 12.0, 0=fill data	1.6	12.1	0
Group	BlackBodyPixels (Size 11264x2 sets per band, 64 pixels per set)					
b1_blackbody_325	UInt16	DN	B1 SWIR Dark Current FPA DN of 325k BB	0	32767	0xffff
b1_blackbody_295	UInt16	DN	B1 SWIR Dark Current FPA DN of 295k BB	0	32767	0xffff
b2_blackbody_325	UInt16	DN	B2 Focal Plane DN of 325k BB	0	32767	0xffff
b2_blackbody_295	UInt16	DN	B2 Focal Plane DN of 295k BB	0	32767	0xffff
b3_blackbody_325	UInt16	DN	B3 Focal Plane DN of 325k BB	0	32767	0xffff
b3_blackbody_295	UInt16	DN	B3 Focal Plane DN of 295k BB	0	32767	0xffff
b4_blackbody_325	UInt16	DN	B4 Focal Plane DN of 325k BB	0	32767	0xffff
b4_blackbody_295	UInt16	DN	B4 Focal Plane DN of 295k BB	0	32767	0xffff
b5_blackbody_325	UInt16	DN	B5 Focal Plane DN of 325k BB	0	32767	0xffff
b5_blackbody_295	UInt16	DN	B5 Focal Plane DN of 295k BB	0	32767	0xffff
b6_blackbody_325	UInt16	DN	B6 Focal Plane DN of 325k BB	0	32767	0xffff

b6_blackbody_295	UInt16	DN	B6 Focal Plane DN of 295k BB	0	32767	0xffff
Group rtdBlackbodyGradients (copied from L1A_ENG file)						
RTD_325K	Float32	Kelvin	5 temperature measurements from back of HBB	310	330	N/A
RTD_295K	Float32	Kelvin	5 temperature measurements from back of CBB	275	305	N/A
Time_j2000	Float64	Seconds	J2000 times of temperature reading and HK packet	N/A	N/A	N/A

units, valid_min, valid_max, and fill values are provided in HDF5 dataset attributes

L1A_PIX - Raw Pixel Data with FPA Blackbody Temperature and Processed FPA BlackBody Band DNs

Table 3-5: Product Data Definitions

Field Name	Type	Units	Field Data	valid min	valid max	fill
Group	L1A_PIXMetadata					
QAPercentMissingData	Float32	%	Percentage of data missing from L0B	0	100	N/A
BandSpecification	Float32	µm	Wavelength of BB pixel data in corresponding datasets for bands 1 through 6: 1.6, 8.2, 8.7,9.0, 10.5, 12.0; 0=fill data	1.6	12.1	0
Group	UncalibratedDN (Size 11264x5400 sets)					
b1_image	Int16	DN	Band 1 SWIR Raw image Pixel Data	0	32767	Table 3-7
b2_image	Int16	DN	Band 2 Raw image Pixel Data	0	32767	Table 3-7
b3_image	Int16	DN	Band 3 Raw image Pixel Data	0	32767	Table 3-7
b4_image	Int16	DN	Band 4 Raw image Pixel Data	0	32767	Table 3-7
b5_image	Int16	DN	Band 5 Raw image Pixel Data	0	32767	Table 3-7
b6_image	Int16	DN	Band 6 Raw image Pixel Data	0	32767	Table 3-7
Group	BlackbodyTemp (1 set for image frame)					
fpa_325	Float32	Kelvin	Calibrated 325 Kelvin Blackbody Focal Plane	310	330	N/A
fpa_295	Float32	Kelvin	Calibrated 295 Kelvin Blackbody Focal Plane	275	305	N/A
Group	BlackbodyBandDN (1 set for image frame)					
b1_325	Float32	DN	B1 Focal Plane Averaged DN for 325k BB	0	32767	Table 3-7
b1_295	Float32	DN	B1 Focal Plane Averaged DN for 295k BB	0	32767	Table 3-7
b2_325	Float32	DN	B2 Focal Plane Averaged DN for 325k BB	0	32767	Table 3-7
b2_295	Float32	DN	B2 Focal Plane Averaged DN for 295k BB	0	32767	Table 3-7
b3_325	Float32	DN	B3 Focal Plane Averaged DN for 325k BB	0	32767	Table 3-7
b3_295	Float32	DN	B3 Focal Plane Averaged DN for 295k BB	0	32767	Table 3-7
b4_325	Float32	DN	B4 Focal Plane Averaged DN for 325k BB	0	32767	Table 3-7
b4_295	Float32	DN	B4 Focal Plane Averaged DN for 295k BB	0	32767	Table 3-7
b5_325	Float32	DN	B5 Focal Plane Averaged DN for 325k BB	0	32767	Table 3-7
b5_295	Float32	DN	B5 Focal Plane Averaged DN for 295k BB	0	32767	Table 3-7
b6_325	Float32	DN	B6 Focal Plane Averaged DN for 325k BB	0	32767	Table 3-7
b6_295	Float32	DN	B6 Focal Plane Averaged DN for 295k BB	0	32767	Table 3-7
Group	FPIEncoder (Size 44x5400)					
EncoderValue	UInt32	None	Mirror encoder value of each focal plane in each scan	0	1749247	0xffffffff
Group	Time (Size 11264x1, 44 scans, 256 repeated values per scan)					
line_start_time_j2000	Float64	Second	J2000 time of first pixel in line	N/A	N/A	N/A

The b1_image through b6_image use special values to indicate bad/missing data.

Table 3-7: Special Image Data Values

Data Condition	Value
Missing data due to striping	-9998
Other missing/bad data	-9999

3.3.3 L1B_RAD - Radiometrically Corrected and Resampled At-Sensor Radiances

Table 3-8: Product Data Definitions

Field Name	Type	Units	Field Data	valid min	valid max	Fill
Group	Radiance (Size 5632x5400 sets)					
radiance_1	Float32	Watt/m2/sr/um	TIR 8.285 microns.	N/A	N/A	Table 3-10
radiance_2	Float32	Watt/m2/sr/um	TIR 8.785 microns	N/A	N/A	Table 3-10
radiance_3	Float32	Watt/m2/sr/um	TIR 9.060 microns	N/A	N/A	Table 3-10
radiance_4	Float32	Watt/m2/sr/um	TIR 10.522 microns	N/A	N/A	Table 3-10
radiance_5	Float32	Watt/m2/sr/um	TIR 12.001 microns	N/A	N/A	Table 3-10
data_quality_1	Int8	None		0	4	N/A
data_quality_2	Int8	None		0	4	N/A
data_quality_3	Int8	None		0	4	N/A
data_quality_4	Int8	None		0	4	N/A
data_quality_5	Int8	None		0	4	N/A
Group	SWIR (Size 5632x5400)					
swir_dn	Int16	DN	Resampled image Pixel Data with Deprecated Counts Correction	N/A	N/A	Table 3-7
Group	FPIEncoder (Size 44x5400)					
EncoderValue	UInt32	None	Mirror encoder value of each focal plane in each scan	0	1749247	0xffffffff
Group	Time (Size 5632, 44 sets of 128 repeated values)					
line_start_time_j2000	Float64	Second	J2000 time of first pixel in line	N/A	N/A	N/A
Group	L1B_RADMetadata					
RadScanLine Order	String	None	One of "Reverse line order" or "Line order". Indicates if we have reversed the order line order for each scan to produce image with separate scans aligned.	N/A	N/A	N/A

The data_quality_1 through data_quality_5 indicates the quality of the radiance_1 through radiance_5 data. It uses the values:

Table 3-9: Data Quality Values

Data Quality/Condition	Value
Good	0
Missing stripe data, filled in	1
Missing stripe data, not filled in	2
Missing/bad data	3
Not seen ¹	4

¹ By the design of the ECOSTRESS instruments, bands don't see a particular cross scan pixel at the same time. When we coregister bands to the reference band, the difference can be large enough that the ISS has moved enough that we miss a pixel at the edges of the scanner. So the data is missing, but by instrument design instead of some kind of a problem with the pixel

In addition, the radiance_1 through radiance_5 use the special values to indicate bad/missing data.

Table 3-10: Special Radiance Data Values

Data Condition	Value
Pixel is not seen ²	-9997.0
Missing data due to striping (not filled in)	-9998.0
Missing/bad data	-9999.0

For swir_dn data, we have the special values used to indicate bad/missing data

Table 3-11: Special SWIR Image Data Values

Data Condition	Value
Pixel is not seen	-9997
Missing data due to striping	-9998
Other missing/bad data	-9999

3.3.4 L1B_GEO – Latitude and Longitude Geolocations, solar and view angles

Table 3-12: Product Data Definitions

Field Name	Type	Units	Field Data	valid min	valid max	fill
Group	Geolocation (Size 5632x5400 sets)					
height	Float32	Meter		N/A	N/A	N/A
land_fraction	Float32	%	Percentage of pixel that is land	0	100	-9999
latitude	Float64	Degrees		-90	90	N/A
line_start_time_j2000	Float64	Second	J2000 time of first pixel in line	N/A	N/A	N/A
longitude	Float64	Degrees		-180	180	N/A
solar_azimuth	Float32	Degrees		-180	180	N/A
solar_zenith	Float32	Degrees		-90	90	NA
view_azimuth	Float32	Degrees		-180	180	N/A
view_zenith	Float32	Degrees		-90	90	N/A
Group	L1GEOMetadata			-90	90	N/A
AverageSolarZenith	Float64	Degrees	Average solar zenith angle for scene			
OrbitCorrectionPerformed	String	None	One of "True" or "False". If "True", we were able to use image matching with our global orthobase to correct the reported navigation. If false, we are using uncorrected navigation data.	N/A	N/A	N/A
OverAllLandFraction	Float64	%	Overall land fraction for scene	0	100	N/A

² See previous footnote for details

3.3.5 L1B_ATT - Corrected spacecraft ephemeris and attitude data

Table 3-13: Product Data Definitions

Field Name	Type	Units	Field Data	valid min	valid max	fill
Group	Ephemeris (Size unlimited, once per second for entire orbit)					
time_j2000	Float64	Seconds	Seconds from J2000 epoch	N/A	N/A	N/A
eci_position	Float64	Meters	X, Y, Z Position in ECI coordinate	N/A	N/A	N/A
eci_velocity	Float64	m/s	X, Y, Z Velocity in ECI coordinates	N/A	N/A	N/A
Group	Attitude (Size unlimited, once per second for entire orbit)					
time_j2000	Float64	Seconds	Seconds from J2000 epoch	N/A	N/A	N/A
quaternion	Float64	None	Attitude quaternion (l, j, k, theta)	N/A	N/A	N/A
Group	Uncorrected Ephemeris (Size unlimited, once per second for entire orbit)					
time_j2000	Float64	Seconds	Seconds from J2000 epoch	N/A	N/A	N/A
eci_position	Float64	Meters	X, Y, Z Position in ECI coordinate	N/A	N/A	N/A
eci_velocity	Float64	m/s	X, Y, Z Velocity in ECI coordinates	N/A	N/A	N/A
Group	Uncorrected Attitude (Size unlimited, once per second for entire orbit)					
time_j2000	Float64	Seconds	Seconds from J2000 epoch	N/A	N/A	N/A
quaternion	Float64	None	Attitude quaternion (l, j, k, theta)	N/A	N/A	N/A
Group	L1GEOMetadata					
OrbitCorrectionPerformed	String	None	One of "True" or "False". If "True", we were able to use image matching with our global orthobase to correct the reported navigation. If false, we are using uncorrected navigation data.	N/A	N/A	N/A

The "Uncorrected" data is the ephemeris and attitude as reported by the ISS, before we apply a correction based on image matching with our Landsat ortho-base.

3.3.6 L1B_MAP_RAD - Map projected radiance

Table 3-13: Product Data Definitions

Field Name	Type	Units	Field Data	valid min	valid max	fill
Group	Mapped/MapInformation			N/A	N/A	N/A
CoordinateSystem	String	None	Well Known Text (WKT) describing coordinate system			
GeoTransform	Float64	None	Affine GeoTransform	N/A	N/A	N/A
Group	Mapped					
data_quality_1	Int8	None		0	4	NA
data_quality_2	Int8	None		0	4	NA
data_quality_3	Int8	None		0	4	NA
data_quality_4	Int8	None		0	4	NA
data_quality_5	Int8	None		0	4	NA
height	Float32	Meters		N/A	N/A	N/A
latitude	Float64	Degrees		-90	90	NA
longitude	Float64	Degrees		-180	180	NA
radiance_1	Float32	Watt/m2/sr/um	TIR 8.285 microns	N/A	N/A	Table 3-10
radiance_2	Float32	Watt/m2/sr/um	TIR 8.785 microns	N/A	N/A	Table 3-10
radiance_3	Float32	Watt/m2/sr/um	TIR 9.060 microns	N/A	N/A	Table 3-10
radiance_4	Float32	Watt/m2/sr/um	TIR 10.522 microns	N/A	N/A	Table 3-10
radiance_5	Float32	Watt/m2/sr/um	TIR 12.001 microns	N/A	N/A	Table 3-10
solar_azimuth	Float32	Degrees		-180	180	N/A
solar_zenith	Float32	Degrees		-90	90	N/A
swir_dn	Int16	DN	Resampled image Pixel Data with Deprecated Counts Correction	NA	NA	Table 3-7
view_azimuth	Float32	Degrees		-180	180	N/A
view_zenith	Float32	Degrees		-90	90	N/A
Group	L1GEOMetadata					
OrbitCorrectionPerformed	String	None	One of "True" or "False". If "True", we were able to use image matching with our global orthobase to correct the reported navigation. If false, we are using uncorrected navigation data.	N/A	N/A	N/A
QAPercentMissingData	Float32	%	Percentage of data missing from L0B	0	100	N/A
BandSpecification	Float32	μm	Wavelength of BB pixel data in corresponding datasets for bands 1 through 6: 1.6, 8.2, 8.7,9.0, 10.5, 12.0; 0=fill data	1.6	12.1	0

We specify the Map Information by giving the Coordinate System an Affine GeoTransform. The Coordinate System is specified as OpeGIS Well Known Text strings (see for example https://en.wikipedia.org/wiki/Well-known_text or http://www.gdal.org/gdal_datamodel.html). This is given in the CoordinateSystem metadata.

We also specify the Affine GeoTransform (as for example in geotiff, see <http://geotiff.maptools.org/spec/geotiff2.6.html> or GDAL, see http://www.gdal.org/gdal_datamodel.html). This is given in the GeoTransform. We have:

$$\begin{aligned}\text{longitude} &= \text{GT}_0 + \text{GT}_1 i + \text{GT}_2 j \\ \text{latitude} &= \text{GT}_3 + \text{GT}_4 i + \text{GT}_5 j\end{aligned}$$

Where (i,j) is the sample, line of the pixel (starting at 0) and longitude and latitude are given in degrees.

Note that in addition, we have the latitude and longitude fields in the file. This is completely redundant with the map projection information, we supply these fields as a convenience for software that expects this data. But you can directly calculate latitude and longitude from the map information.

3.4 Product Metadata File

The product metadata for each product file will be generated by the PCS from the metadata contents of each product file. The metadata will be converted into extensible markup language (XML). These will be used by the DAAC for cataloging.

4.0 APPENDIX A: INTERMEDIATE AND NON-DELIVERED PRODUCTS

4.1 Intermediate, Temporary, and other non-delivered products

The following groups define formats of various intermediate and temporary products generated and used by L1 PGEs, but are not standard products that are delivered to the DAAC. Image band order:

- B1 SWIR 1.66 microns
- B2 TIR 8.285 microns
- B3 TIR 8.785 microns
- B4 TIR 9.060 microns
- B5 TIR 10.522 microns
- B6 TIR 12.001 microns

4.1.1 L1A_RAW_PIX – Raw Scene Pixel Data

Table 4-2: Product Data Definitions

Field Name	Type	Units	Field Data
Group	Standard Metadata (as defined above)		
Group	L1A_RAW_PIXMetadata		
AncillaryFiles	Char	None	N/A
QAPercentMissingData	Float32	%	Number of missing pixels per total pixels in scene (11264*5400)
ISS_time	Float64	Sec	GPS time of ISS time correction element
ISS_time_dpuio	Int64	Counts	Snapshot of FPIE 1 MHz when time_error_correction was recorded
ISS_time_error_correction	Float64	Sec	ISS time correction element to be subtracted from FLEX packet times
Group	UncalibratedPixels (Size 11264x5400 per band)		
pixel_data_1	UInt16	None	Band 1 SWIR scene data
pixel_data_2	UInt16	None	Band 2 TIR scene data
pixel_data_3	UInt16	None	Band 3 TIR scene data
pixel_data_4	UInt16	None	Band 4 TIR scene data
pixel_data_5	UInt16	None	Band 5 TIR scene data
pixel_data_6	UInt16	None	Band 6 TIR scene data
Group	Time (Size 11264x1)		
line_start_time_j2000	Float64	Second	J2000 time of first focal plane of each scan (256 lines by 6 bands per scan)
Group	FPIEncoder (Size 44x5400)		
EncoderValue	UInt32	None	Mirror encoder value of each focal plane in each scan (256 lines by 6 bands)

4.1.2 L1A_RAW_ATT - Uncorrected Spacecraft Ephemeris and Attitude Data

Table 4-3: Product Data Definitions

Field Name	Type	Units	Field Data
Group	Ephemeris (Size unlimited, one set per second for entire orbit)		
time_j2000	Float64	Seconds	Seconds from J2000 epoch
eci_position	3*Float64	Meters	X, Y, Z Position in ECI coordinates
eci_velocity	3*Float64	m/s	X, Y, Z Velocity in ECI coordinates
Group	Attitude		
time_j2000	Float64	Seconds	Seconds from J2000 epoch
Quaternion	4*Float64	None	Attitude quaternion (l, j, k, theta)

4.1.3 L1A_RAD_GAIN – Gain and offset coefficients and optional radiance and temperature Images

Table 4-4: Product Data Definitions

Field Name	Type	Units	Field Data
Group	Gain (Size 11264x5400)		
b1_gain	Float32	Watt/m2/sr/um/DN	Band 2 Gain
b2_gain	Float32	Watt/m2/sr/um/DN	Band 3 Gain
b3_gain	Float32	Watt/m2/sr/um/DN	Band 4 Gain
b4_gain	Float32	Watt/m2/sr/um/DN	Band 5 Gain
b5_gain	Float32	Watt/m2/sr/um/DN	Band 6 Gain
Group	Offset (Size 11264x5400)		
b1_offset	Float32	Watt/m2/sr/um/DN	Band 2 Offset
b2_offset	Float32	Watt/m2/sr/um/DN	Band 3 Offset
b3_offset	Float32	Watt/m2/sr/um/DN	Band 4 Offset
b4_offset	Float32	Watt/m2/sr/um/DN	Band 5 Offset
b5_offset	Float32	Watt/m2/sr/um/DN	Band 6 Offset
Group	SWIR (Size 11264x5400)		
b6_dcc	Int16	DN	Band 1 SWIR Raw image Pixel Data with Deprecated Counts Correction
Group	Rad (Size 11264x5400)		
b1_rad	Float32	Watt/m2/sr/um	Band 2 Radiance
b2_rad	Float32	Watt/m2/sr/um	Band 3 Radiance
b3_rad	Float32	Watt/m2/sr/um	Band 4 Radiance
b4_rad	Float32	Watt/m2/sr/um	Band 5 Radiance
b5_rad	Float32	Watt/m2/sr/um	Band 6 Radiance
Group	Temp (Size 11264x5400)		
b1_temp	Float32	Kelvin	Band 2 Temperature Kelvin
b2_temp	Float32	Kelvin	Band 3 Temperature Kelvin
b3_temp	Float32	Kelvin	Band 4 Temperature Kelvin
b4_temp	Float32	Kelvin	Band 5 Temperature Kelvin
b5_temp	Float32	Kelvin	Band 6 Temperature Kelvin

4.1.4 L1B_GEO_QA – QA data for L1B_GEO PGE

Table 4-5: Product Data Definitions

Field Name	Type	Units	Field Data
Average Metadata	Float64	None	Various averages for each scene. First column is solar zenith angle, second is land fraction
Input File List	String	None	Full list of input files, including paths, that we ran with
Group	Accuracy Estimate		
Accuracy Before Correction	Float64	Meter	Accuracy estimate for each scene before correction
Final Accuracy	Float64	Meter	Accuracy estimate after correction
Scene	String	None	List of scenes included in accuracy estimate
OrbitCorrectionPerformed	String	None	One of "True" or "False". If "True", we were able to use image matching with our global orthobase to correct the reported navigation. If false, we are using uncorrected navigation data.
Group	Logs		
Encountered Exception	String	None	One of "True" or "False". True if we encountered an exception in processing
Overall Log	String	None	Log file for full process
Group	Logs/Tiepoint Logs		
Scene 1	String	None	Log file for Scene 1 Tiepoint
Scene 2	String	None	Log file for Scene 2 Tiepoint
...	String	None	Log file for each scene
Group	Orbit		
Attitude Correction	Float64	Arcseconds	
Attitude Time Point	Float64	Seconds	J2000 time of attitude correction
Position Correction	Float64	Meters	
Position Time Point	Float64	Seconds	J2000 time of position correction
Group	PythonObject		
igccol_initial	String	None	XML file describing initial igccol
igccol_initial_desc	String	None	Text describing initial igccol
igccol_sba	String	None	XML file describing igccol after sba
igccol_sba_desc	String	None	Text describing igccol after sba
tpcol	String	None	XML file describing initial tie-points
tpcol_desc	String	None	Text describing initial tie-points
tpcol_sba	String	None	XML file describing tie-points after sba
tpcol_sba_desc	String	None	Text describing tie-points after sba
Group	Tiepoint		
Scene	String	None	List of scenes we collect tie-point for

Tiepoint Count	int32	None	Count of tie-points for each scene
Group	Tiepoint/Scene 1		
Tiepoints Dataset	float64	None	Tie-points collected for scene 1
Group	Tiepoint/Scene 2		
Tiepoints Dataset	float64	None	Tie-points collected for scene 2
Group	Tiepoint/Scene....		
Tiepoints Dataset	float64	None	Tie-points collected for each scene

APPENDIX B: ABBREVIATIONS AND ACRONYMS

ALEXI	Atmospheric-Land Exchange Inversion
ARS	Agricultural Research Service
ASD	Algorithm Specifications Document
ATBD	Algorithm Theoretical Basis Document
CCB	Change Control Board
CDR	Critical Design Review
CF	Climate and Forecast (metadata convention)
CM	Configuration Management
CONUS	Continental United States
COTS	Commercial Off The Shelf
DAAC	Distributed Active Archive Center
dB	DeciBel
DCN	Document Change Notice
deg	Degrees
deg/sec	Degrees per Second
DEM	Digital Elevation Model
DisALEXI	ALEXI Disaggregation algorithm
DN	Data Number
EASE	Equal Area Scalable Earth
ECI	Earth Centered Inertial coordinate system
ECR	Earth Centered Rotating coordinate system
ECS	EOSDIS Core System
ECOSTRESS	ECOSystem Spaceborne Thermal Radiometer on Space Station
EOS	Earth Observing System
EOSDIS	EOS Data and Information System
ESDIS	Earth Science Data and Information System
ESDT	Earth Science Data Type
FOV	Field of View
FSW	Flight Software
GB	gigabytes, 10 ⁹ bytes
GDS	Ground Data System
GHA	Greenwich Hour Angle
GHz	Gigahertz, 10 ⁹ hertz
GMAO	Global Modeling and Assimilation Office
GMT	Greenwich Mean Time
GPP	Gross Primary Production
GSE	Ground Support Equipment
GSFC	Goddard Space Flight Center
HDF	Hierarchical Data Format
HK	Housekeeping (telemetry)
HRSL	Hydrology and Remote Sensing Laboratory
Hz	Hertz
HSD	Health and Status Data
I&T	Integration and Test
ICD	Interface Control Document
I/O	Input/Output
IOC	In-Orbit Checkout

IPA	Inter-Project Agreement
JPL	Jet Propulsion Laboratory
K	Kelvin
KHz	Kilohertz
Km	kilometer, 1000 meters
L0 – L4	Level 0 through Level 4
LAN	Local Area Network
LEO	Low Earth Orbit
LOE	Level of Effort
LOM	Life of Mission
LP	Land Processes
LSTE	Land Surface Temperature and Emissivity
m	meter
MB	megabytes, 10 ⁶ bytes
Mbps	Mega bits per second
MHz	Megahertz
MMR	Monthly Management Review
MOA	Memorandum of Agreement
MODIS	Moderate Resolution Imaging Spectroradiometer
MOS	Mission Operations System
m/s	meters per second
ms	milliseconds
MS	Mission System
NASA	National Aeronautics and Space Administration
NCEP	National Centers for Environmental Protection
NCSA	National Center for Supercomputing Applications
netCDF	Network Common Data Format
NISN	NASA Integrated Services Network
NOAA	National Oceanic and Atmospheric Administration
OA	Operations Agreement
ODL	Object Description Language
ODT	Object Oriented Data Technology
ORR	Operational Readiness Review
ORT	Operational Readiness Test
PDR	Preliminary Design Review
percent	%, per hundred
PR	Problem Report
PSD	Product Specifications Document
PT-JPL	Priestly-Taylor-JPL
QA	Quality Assurance
rad	radians
RDD	Release Description Document
RFA	Request For Action
S/C	Spacecraft
SCP	Secure Copy
SDP	Software Development Plan
SDS	Science Data System
sec, s	seconds
SITP	System Integration and Test Plan
SMP	Software Management Plan

SOM	Software Operators Manual
TAI	International Atomic Clock
T _b	Brightness Temperature
TBD	To Be Determined
TBS	To Be Specified
TOA	Time of Arrival
TPS	Third Party Software
USDA	United State Department of Agriculture
USGS	United States Geological Society
UTC	Coordinated Universal Time
V&V	Verification and Validation
XML	Extensible Markup Language